```
c============================================================
c     bisect: Uses bisection to find approximate root
c     of f(x) on interval [xmin .. xmax].  Return value is
c     root located to (relative) tolerance 'xtol'.  Return code
c     'rc' is set to 0 on success, non-zero on failure
c     and routine succeeds (by definition) as long as initial
c     interval *does* bracket at least one root.  Routine
c     performs tracing of algorithm (on stderr) if input
c     argument 'trace' is .true.
c============================================================
      real*8 function bisect(f,xmin,xmax,xtol,trace,rc)

         implicit     none

         real*8       drelabs

         real*8       f
         external     f

         real*8       xmin,          xmax,         xtol
         logical      trace
         integer      rc
c------------------------------------------------------------
c        Other variables needed for search.
c------------------------------------------------------------
         integer      mxiter
         parameter  ( mxiter = 50 )

         real*8       xlo,           dx,           sfxmid,
     &                sgn
         integer      iter
```

```
c-----------------------------------------------------------
c        Check that input interval is specified correctly
c        and that it manifestly brackets at least one root:
c        (i.e. the fcn changes sign).
c-----------------------------------------------------------
         if( xmax .le. xmin  .or.
     &        f(xmin) * f(xmax) .gt. 0.0d0 ) then
            write(0,*) 'bisect:  Input interval is not '//
     &                 'bracketing'
            rc = 1
c-----------------------------------------------------------
c           Returned value is meaningless in this case,
c           but have to return *some* value.
c-----------------------------------------------------------
            bisect = xmin
            return
         end if
c-----------------------------------------------------------
c        Compute 'sgn' such that sgn * f(xmin) < 0, and
c        intialize bracketing interval
c-----------------------------------------------------------
         sgn  = 1.0d0
         if( f(xmin) .le. 0.0d0 ) then
            sgn =  1.0d0
         else
            sgn = -1.0d0
         end if
         xlo  = xmin
         dx   = xmax - xmin
```

```
c-------------------------------------------------------------
c        Bisection loop: continue until root found to
c        specfied tolerance or until maximum number of
c        iterations taken
c-------------------------------------------------------------
         do iter = 1 , mxiter
            bisect = xlo + 0.5d0 * dx
            if( trace ) then
               write(0,*) xlo, xlo + dx, f(bisect)
            end if
            if( sgn * f(bisect) .lt. 0.0d0 ) then
               xlo = bisect
            end if
            if( drelabs(dx,bisect,1.0d-10) .le. xtol ) go to 900
            dx = 0.5d0 * dx
         end do

900      continue
         rc = 0
         if( trace ) write(0,*)
         return

      end
```

```
c=============================================================
c     drelabs:  Function useful for 'relativizing' quantity
c     being monitored for detection of convergence.
c=============================================================
      real*8 function drelabs(dx,x,xfloor)
         implicit      none

         real*8        dx,     x,    xfloor

         if( abs(x) .lt. abs(xfloor) ) then
            drelabs = abs(dx)
         else
            drelabs = abs(dx/x)
         end if

         return
      end
```

```
c=============================================================
c     tbisect: Illustrates root finding using bisection
c     routine 'bisect'.
c
c     Initial bracketing interval must be specified via the
c     command-line, along with optional convergence criteria
c     and output option.
c
c     This program also illustrates the general Fortran
c     techniques (briefly discussed previously) for:
c
c     (1) Writing and using routines which take other routines
c     as arguments.
c     (2) Using a COMMON block to communicate information to
c     a routine in cases where the information cannot be
c     passed via the argument list.
c     (3) Using an "INCLUDE" file (in this case 'comf.inc')
c     to ensure that the same common block structure is defined
c     in all program units.
c
c     Currently set up for computing square roots i.e.
c     solves
c
c         f(x; a) = x**2 - a = 0
c
c     for 'a' specifed on command-line
c
c     Outputs a, approximate root (x*) and f(x*; a) on stdout.
c=============================================================
      program         tbisect
      implicit        none
```

```
c-----------------------------------------------------------
c     Declaration of the bisection routine.
c-----------------------------------------------------------
      real*8          bisect
c-----------------------------------------------------------
c     Name of the specific function whose root we seek.
c     Note use of 'external' to let compiler know 'fsqr'
c     is the name of a function, not a variable.
c-----------------------------------------------------------
      real*8          fsqr
      external        fsqr

      integer         i4arg,          iargc
      real*8          r8arg
c-----------------------------------------------------------
c     For use in detecting bad real*8 command-line value.
c-----------------------------------------------------------
      real*8          r8_never
      parameter     ( r8_never = -1.0d-60 )
c-----------------------------------------------------------
c     Use a common block to pass number whose square root
c     is sought to external function 'fsqr'.
c-----------------------------------------------------------
      include        'comf.inc'
c-----------------------------------------------------------
c     Initial bracket, convergence tolerance and output
c     option from command-line; default value for conv.
c     tolerance.
c-----------------------------------------------------------
      real*8          xmin,           xmax,         xtol
      logical         trace

      real*8          default_xtol
      parameter     ( default_xtol = 1.0d-8 )
```

```
c-------------------------------------------------------
c     Root and return code from bisection routine.
c-------------------------------------------------------
      real*8          root
      integer         rc
c-------------------------------------------------------
c     Argument parsing.
c-------------------------------------------------------
      if( iargc() .lt. 3 ) go to 900
      a     = r8arg(1,r8_never)
      xmin  = r8arg(2,r8_never)
      xmax  = r8arg(3,r8_never)
      if( a .eq. r8_never  .or.  xmin .eq. r8_never  .or.
     &    xmax .eq. r8_never ) go to 900

      xtol  = r8arg(4,default_xtol)
      trace = iargc() .gt. 4
c-------------------------------------------------------
c     Invoke root finder then write a, sqrt(a), and residual
c     to standard output.
c-------------------------------------------------------
      root = bisect(fsqr,xmin,xmax,xtol,trace,rc)
      if( rc .eq. 0 ) then
         write(*,*) a, root, fsqr(root)
      else
         write(0,*) 'tbisect: Bisection failed.'
      end if
c-------------------------------------------------------
c     Normal exit.
c-------------------------------------------------------
      stop
```

```
c-------------------------------------------------------------
c     Usage exit.
c-------------------------------------------------------------
 900  continue
         write(0,*) 'usage: tbisect <a> <xmin> <xmax> '//
     &              '[<xtol> <trace>]'
      stop

      end

c=============================================================
c     Function whose root is sought.  Again, note use of
c     COMMON block to pass additional information (in this
c     case 'a') to the routine.
c=============================================================
      real*8 function fsqr(x)
         implicit      none

         real*8        x

         include      'comf.inc'

         fsqr = x**2 - a

         return
      end
```

```
c-------------------------------------------------------------
c     Common block for communicating value of 'a' from main
c     to 'fsqr'.
c-------------------------------------------------------------
      real*8              a
      common    / comf /  a
```

```
#############################################################
# Building 'tbisect' and sample output on sgi1
#
# 'tbisect' is set up to compute sqrt(a) via bisection.
#############################################################

sgi1% pwd ; ls
/usr/people/phys410/nonlin/ex1

Makefile    bisect.f    comf.inc    tbisect.f
sgi1% make
f77 -g -64 -c tbisect.f
f77 -g -64 -c bisect.f
f77 -g -64 -L/usr/local/lib tbisect.o bisect.o -lp410f -o tbisect

sgi1% tbisect
 usage: tbisect <a> <xmin> <xmax> [<xtol> <trace>]

#############################################################
# Compute +sqrt(2) to default tolerance (1.0d-8)
#
# Note: Exact value to 16 digits is 1.414 2135 6237 3095
#############################################################
sgi1% tbisect 2.0 1.0 2.0
 2.000000000000000       1.414213564246893      5.2999009625409599E-09

#############################################################
# Recompute with higher tolerance (1.0d-12)
#############################################################
sgi1% tbisect 2.0 1.0 2.0 1.0e-12
 2.000000000000000       1.414213562372879     -6.1084470814876113E-13
```

```
############################################################
# Enable tracing output by supplying 5th argument.  Note
# supplying a '.' as an argument parsed by 'i4arg' or 'r8arg'
# is equivalent to specifying the default value.
############################################################
sgi1% tbisect 2.0 1.0 2.0 . 1
 1.000000000000000       2.000000000000000      0.2500000000000000
 1.000000000000000       1.500000000000000     -0.4375000000000000
 1.250000000000000       1.500000000000000     -0.1093750000000000
 1.375000000000000       1.500000000000000      6.6406250000000000E-02
 1.375000000000000       1.437500000000000     -2.2460937500000000E-02
 1.406250000000000       1.437500000000000      2.1728515625000000E-02
 1.406250000000000       1.421875000000000     -4.2724609375000000E-04
 1.414062500000000       1.421875000000000      1.0635375976562500E-02
 1.414062500000000       1.417968750000000      5.1002502441406250E-03
 1.414062500000000       1.416015625000000      2.3355484008789063E-03
 1.414062500000000       1.415039062500000      9.5391273498535156E-04
 1.414062500000000       1.414550781250000      2.6327371597290039E-04
 1.414062500000000       1.414306640625000     -8.2001090049743652E-05
 1.414184570312500       1.414306640625000      9.0632587671279907E-05
 1.414184570312500       1.414245605468750      4.3148174881935120E-06
 1.414184570312500       1.414215087890625     -3.8843369111418724E-05
 1.414199829101563       1.414215087890625     -1.7264334019273520E-05
 1.414207458496094       1.414215087890625     -6.4747728174552321E-06
 1.414211273193359       1.414215087890625     -1.0799813026096672E-06
 1.414213180541992       1.414215087890625      1.6174171832972206E-06
 1.414213180541992       1.414214134216309      2.6871771297010127E-07
 1.414213180541992       1.414213657379150     -4.0563185166320181E-07
 1.414213418960571       1.414213657379150     -6.8457083557404985E-08
 1.414213538169861       1.414213657379150      1.0013031115363447E-07
 1.414213538169861       1.414213597774506      1.5836612909936321E-08
 1.414213538169861       1.414213567972183     -2.6310235545778937E-08
 1.414213553071022       1.414213567972183     -5.2368114289436107E-09
 1.414213560521603       1.414213567972183      5.2999009625409599E-09
```

2.000000000000000 1.414213564246893 5.2999009625409599E-09

```
c=============================================================
c     newtsqrt:  Uses Newton's method to find (positive)
c     square root of number supplied on command line, i.e.
c     solves
c
c     f(x) = x^2 - a = 0
c
c     for given 'a'.  Optional second argument specifies
c     convergence criteria (relative dx).
c
c     Tracing output (written to standard error)
c     includes iteration number, estimated root (xn),
c     change in estimate (dxn), log10(dxn), residual and
c     log10(residual).
c=============================================================
      program         newtsqrt

      implicit        none

      integer         iargc
      real*8          r8arg,        drelabs

      real*8          r8_never
      parameter     ( r8_never = -1.0d-60 )
c-------------------------------------------------------------
c     Default convergence tolerance.
c-------------------------------------------------------------
      real*8          default_xtol
      parameter     ( default_xtol = 1.0d-8 )
c-------------------------------------------------------------
c     Maximum allowed number of Newton iterations.
c-------------------------------------------------------------
      integer         mxiter
      parameter     ( mxiter = 50 )
```

```
c-------------------------------------------------------------
c     Command-line arguments (see above).
c-------------------------------------------------------------
      real*8          a,            xtol
c-------------------------------------------------------------
c     Locals used in Newton iteration.
c-------------------------------------------------------------
      integer         iter
      real*8          xn,           resn,           dxn

c-------------------------------------------------------------
c     Argument parsing.
c-------------------------------------------------------------
      if( iargc() .lt. 1 ) go to 900
      a     = r8arg(1,r8_never)
      if( a .eq. r8_never .or. a .lt. 0.0d0 ) go to 900
      xtol  = r8arg(2,1.0d-8)
      if( xtol .le. 0.0d0 ) xtol = 1.0d-8

c-------------------------------------------------------------
c     Un-inspired initial guess: x^(0) = a / 2.
c-------------------------------------------------------------
      xn = 0.5d0 * a
```

```
c-------------------------------------------------------------
c     Newton loop.
c-------------------------------------------------------------
      write(0,*) 'Iter          xn                 '//
     &           'dxn     log10(dxn)    rn       log10(rn)'
      write(0,*)
      do iter = 1 , mxiter
         resn = xn**2 - a
         dxn  = resn / (2.0d0 * xn)
         xn   = xn - dxn
         write(0,1000) iter, xn, dxn, log10(abs(dxn)),
     &                 resn, log10(abs(resn))
1000     format(i2,1p,e26.16,e12.3,0p,f10.2,1p,e12.3,0p,f10.2)
c-------------------------------------------------------------
c        Jump out of Newton loop if soln has converged.
c-------------------------------------------------------------
         if( drelabs(dxn,xn,1.0d-10) .le. xtol ) go to 100
      end do
c-------------------------------------------------------------
c     No-convergence exit.
c-------------------------------------------------------------
      write(0,*) 'No convergence after ', mxiter,
     &           ' iterations'
      stop

c-------------------------------------------------------------
c     Normal exit, write input and estimated square root
c     to standard output.
c-------------------------------------------------------------
 100  continue
      write(0,*)
      write(*,*) a, xn
      stop
```

```
c-------------------------------------------------------------
c     Usage exit.
c-------------------------------------------------------------
 900  continue
         write(0,*) 'usage: newtsqrt <a> [<xtol>]'
      stop

      end

c=============================================================
c     drelabs:  Function useful for 'relativizing' quantity
c     being monitored for detection of convergence.
c=============================================================
      real*8 function drelabs(dx,x,xfloor)

         implicit      none

         real*8        dx,     x,    xfloor

         if( abs(x) .lt. abs(xfloor) ) then
            drelabs = abs(dx)
         else
            drelabs = abs(dx/x)
         end if

         return

      end
```

```
#############################################################
# Building 'newtsqrt' and sample output on sgi1
#############################################################
sgi1% pwd; ls
/usr/people/phys410/nonlin/ex2
Makefile     newtsqrt.f

sgi1% make
f77 -g -64 -c newtsqrt.f
f77 -g -64 -L/usr/local/lib newtsqrt.o -lp410f -o newtsqrt

sgi1% newtsqrt
 usage: newtsqrt <a> [<xtol>]

#############################################################
# Compute +sqrt(10) to default tolerance (1.0d-8)
#
# Note: Exact value to 16 digits is 3.162 2776 6016 8379
#############################################################
sgi1% newtsqrt 10.0
Iter          xn                   dxn    log10(dxn)    rn       log10(rn)

1    3.5000000000000000E+00   1.500E+00     0.18   1.500E+01      1.18
2    3.1785714285714284E+00   3.214E-01    -0.49   2.250E+00      0.35
3    3.1623194221508828E+00   1.625E-02    -1.79   1.033E-01     -0.99
4    3.1622776604441363E+00   4.176E-05    -4.38   2.641E-04     -3.58
5    3.1622776601683795E+00   2.758E-10    -9.56   1.744E-09     -8.76

    10.00000000000000       3.162277660168380
```

```
#############################################################
# Recompute with higher tolerance---an extra Newton step
# is taken, but the solution was already accurate to
# roughly machine epsilon, so there is very little change
# in the output.
#############################################################
sgi1% newtsqrt 10.0 1.0e-15
Iter          xn                  dxn    log10(dxn)    rn       log10(rn)

1    3.5000000000000000E+00   1.500E+00     0.18   1.500E+01      1.18
2    3.1785714285714284E+00   3.214E-01    -0.49   2.250E+00      0.35
3    3.1623194221508828E+00   1.625E-02    -1.79   1.033E-01     -0.99
4    3.1622776604441363E+00   4.176E-05    -4.38   2.641E-04     -3.58
5    3.1622776601683795E+00   2.758E-10    -9.56   1.744E-09     -8.76
6    3.1622776601683791E+00   2.809E-16   -15.55   1.776E-15    -14.75

    10.00000000000000       3.162277660168379

#############################################################
# Compute +sqrt(1/2) to default tolerance (1.0d-8)
#
# Note: Exact value to 16 digits is 0.7071 0678 1186 5475
#############################################################
sgi1% newtsqrt 0.5
Iter          xn                  dxn    log10(dxn)    rn       log10(rn)

1    1.1250000000000000E+00  -8.750E-01    -0.06  -4.375E-01     -0.36
2    7.8472222222222221E-01   3.403E-01    -0.47   7.656E-01     -0.12
3    7.1094518190757128E-01   7.378E-02    -1.13   1.158E-01     -0.94
4    7.0711714297003669E-01   3.828E-03    -2.42   5.443E-03     -2.26
5    7.0710678126246607E-01   1.036E-05    -4.98   1.465E-05     -4.83
6    7.0710678118654757E-01   7.592E-11   -10.12   1.074E-10     -9.97

   0.5000000000000000      0.7071067811865476
```

```
c=============================================================
c     newt2:  Uses multi-dimensional Newton's method
c     to compute a root of simple non-linear system
c     discussed in class
c
c        sin(xy) - 1/2 = 0
c        y^2 - 6x - 2  = 0
c
c     Command line input is initial guess (two numbers)
c     for root, and optional convergence criteria.
c     Estimated root written to standard output.
c     Tracing output similar to that from 'newtsqrt'.
c=============================================================
      program         newt2

      implicit        none

      integer         iargc
      real*8          r8arg,        drelabs,      dvl2norm

      real*8          r8_never
      parameter     ( r8_never = -1.0d-60 )
c-------------------------------------------------------------
c     Size of system.
c-------------------------------------------------------------
      integer         neq
      parameter     ( neq = 2 )
c-------------------------------------------------------------
c     Command-line arguments:  Initial guess will be
c     input directly into 'x' array.
c-------------------------------------------------------------
      real*8          tol
```

```
c-------------------------------------------------------------
c     Variables used in Newton iteration and solution of
c     linear systems via LAPACK routine 'dgesv'.
c-------------------------------------------------------------
      real*8          J(neq,neq),   res(neq),
     &                x(neq)
      integer         ipiv(neq)
      integer         ieq,          info

      integer         mxiter,       nrhs
      parameter     ( mxiter = 50,  nrhs = 1 )

      integer         iter
      real*8          nrm2res,      nrm2dx,      nrm2x
c-------------------------------------------------------------
c     Default convergence tolerance.
c-------------------------------------------------------------
      real*8          default_tol
      parameter     ( default_tol = 1.0d-8 )
c-------------------------------------------------------------
c     Argument parsing.
c-------------------------------------------------------------
      if( iargc() .lt. neq ) go to 900
      do ieq = 1 , neq
         x(ieq) = r8arg(ieq,r8_never)
         if( x(ieq) .eq. r8_never ) go to 900
      end do
      tol  = r8arg(neq+1,default_tol)
      if( tol .le. 0.0d0 ) tol = default_tol
```

```
c-----------------------------------------------------------
c     Newton loop.
c-----------------------------------------------------------
      write(0,*) 'Iter           x                      y '//
     &           '          log10(dx) log10(res)'
      write(0,*)
      do iter = 1 , mxiter
c-----------------------------------------------------------
c        Evaluate residual vector.
c-----------------------------------------------------------
         res(1) = sin(x(1)*x(2)) - 0.5d0
         res(2) = x(2)**2 - 6.0d0 * x(1) - 2.0d0
         nrm2res = dvl2norm(res,2)
c-----------------------------------------------------------
c        Set up Jacobian.
c-----------------------------------------------------------
         J(1,1) = x(2) * cos(x(1) * x(2))
         J(1,2) = x(1) * cos(x(1) * x(2))
         J(2,1) = -6.0d0
         J(2,2) = 2.0d0 * x(2)
c-----------------------------------------------------------
c        Solve linear system (J dx = res) for update
c        dx.  Update returned in 'res' vector.
c-----------------------------------------------------------
         call dgesv( neq, nrhs, J, neq, ipiv, res, neq, info )
         if( info .eq. 0 ) then
c-----------------------------------------------------------
c           Update solution.
c-----------------------------------------------------------
            nrm2x  = dvl2norm(x,neq)
            nrm2dx = dvl2norm(res,neq)
            do ieq = 1 , neq
               x(ieq) = x(ieq) - res(ieq)
            end do
```

```
c-------------------------------------------------------
c           Tracing output: note use of max to prevent
c           taking log10 of 0.
c-------------------------------------------------------
            write(0,1000) iter, x(1), x(2),
     &                    log10(max(nrm2dx,1.0d-60)),
     &                    log10(max(nrm2res,1.0d-60))
1000        format(i2,1p,2e24.16,0p,2f8.2)
c-------------------------------------------------------
c           Check for convergence.
c-------------------------------------------------------
            if( drelabs(nrm2dx,nrm2x,1.0d-6) .le. tol ) go to 100
         else
            write(0,*) 'newt2: dgesv failed.'
            stop
         end if
      end do
c-------------------------------------------------------
c     No-convergence exit.
c-------------------------------------------------------
      write(0,*) 'No convergence after ', mxiter,
     &           ' iterations'
      stop

c-------------------------------------------------------
c     Normal exit, write input and estimated square root
c     to standard output.
c-------------------------------------------------------
 100  continue
      write(0,*)
      write(*,*) x
      stop
```

```
c-------------------------------------------------------------
c     Usage exit.
c-------------------------------------------------------------
 900  continue
         write(0,*) 'usage: newt2 <x0> <y0> [<tol>]'
      stop

      end

c=============================================================
c     dvl2norm:  Returns l2-norm of double precision vector.
c=============================================================
      real*8 function dvl2norm(v,n)

         implicit      none

         integer       n
         real*8        v(n)
         integer       i

         dvl2norm = 0.0d0
         do i = 1 , n
            dvl2norm = dvl2norm + v(i) * v(i)
         end do
         if( n .gt. 0 ) then
            dvl2norm = sqrt(dvl2norm / n)
         end if

         return

      end
```

```
c=============================================================
c     drelabs:  Function useful for 'relativizing' quantity
c     being monitored for detection of convergence.
c=============================================================
      real*8 function drelabs(dx,x,xfloor)

         implicit      none

         real*8        dx,     x,    xfloor

         if( abs(x) .lt. abs(xfloor) ) then
            drelabs = abs(dx)
         else
            drelabs = abs(dx/x)
         end if

         return

      end
```

```
################################################################
# Building 'newt2' and sample output on sgi1.
#
# Note how different roots are found depending on the initial
# guess and how, in each case, convergence of both dx and
# the residual is quadratic as the solution is approached.
################################################################
sgi1% pwd ; ls
/usr/people/phys410/nonlin/ex3
Makefile   newt2.f

sgi1% make
f77 -g -64 -c newt2.f
f77 -g -64 -L/usr/local/lib newt2.o -lp410f -llapack -lblas -o newt2

sgi1% newt2
 usage: newt2 <x0> <y0> [<tol>]

################################################################
# Start with initial guess (1.0,1.0) and use default tolerance
################################################################
sgi1% newt2 1.0 1.0
 Iter           x                      y           log10(dx) log10(res)

 1 -3.2999966453609808E-02  1.4010001006391706E+00   -0.11    0.70
 2  3.7660093320946680E-01  2.2207017966697333E+00   -0.19   -0.40
 3  2.6508349149835875E-01  1.9187667230923000E+00   -0.64   -0.30
 4  2.7416951525985472E-01  1.9092166705387068E+00   -2.03   -1.19
 5  2.7423631305849172E-01  1.9092977465351673E+00   -4.13   -3.95
 6  2.7423631371214585E-01  1.9092977458408302E+00   -9.17   -8.33

   0.2742363137121459       1.909297745840830
```

```
#################################################################
# Start with initial guess (10.0,10.0)
#################################################################
sgi1% newt2 10.0 10.0
 Iter           x                      y           log10(dx) log10(res)

 1  1.1551311217431483E+01  8.5653933652294452E+00    0.17    1.43
 2  5.2821340061728987E+00  6.2494950887340917E+00    0.67    0.26
 3  7.9156169056753551E+00  7.0845635560056479E+00    0.29    0.58
 4  8.0553488926886114E+00  7.0945184795470357E+00   -1.00   -0.08
 5  8.0478800969936373E+00  7.0913532277542579E+00   -2.24   -1.34
 6  8.0480621354266173E+00  7.0914295327798440E+00   -3.86   -2.93
 7  8.0480622340064549E+00  7.0914295740731097E+00   -7.12   -6.20

    8.048062234006455       7.091429574073110

#################################################################
# Start with initial guess (100.0,100.0)
#################################################################
sgi1% newt2 100.0 100.0
 Iter           x                      y           log10(dx) log10(res)

 1  1.4561314470371522E+02  5.4378394341111459E+01    1.66    3.82
 2  1.9021837653952511E+02  3.7701738714769540E+01    1.53    3.17
 3  2.0349983567820649E+02  3.5070267397907145E+01    0.98    2.29
 4  2.0392234856561154E+02  3.5007684984188487E+01   -0.52    0.70
 5  2.0390326095147395E+02  3.5005993323580455E+01   -1.87   -0.53
 6  2.0391023928640132E+02  3.5006591323292412E+01   -2.31   -0.59
 7  2.0391061250942661E+02  3.5006623302706338E+01   -3.58   -1.92
 8  2.0391061457091234E+02  3.5006623479357074E+01   -5.83   -4.18
 9  2.0391061457097669E+02  3.5006623479362588E+01  -10.34   -8.68

    203.9106145709767       35.00662347936259
```

```
################################################################
# Start with initial guess (0.0,0.0), generates singular
# Jacobian
################################################################
sgi1% newt2 0.0 0.0
 Iter           x                       y           log10(dx) log10(res)

 newt2: dgesv failed.

################################################################
# Start with initial guess (1.0,1.0) but use more stringent
# tolerance
################################################################
sgi1% newt2 1.0 1.0 1.0e-15
 Iter           x                       y           log10(dx) log10(res)

 1 -3.2999966453609808E-02  1.4010001006391706E+00   -0.11    0.70
 2  3.7660093320946680E-01  2.2207017966697333E+00   -0.19   -0.40
 3  2.6508349149835875E-01  1.9187667230923000E+00   -0.64   -0.30
 4  2.7416951525985472E-01  1.9092166705387068E+00   -2.03   -1.19
 5  2.7423631305849172E-01  1.9092977465351673E+00   -4.13   -3.95
 6  2.7423631371214585E-01  1.9092977458408302E+00   -9.17   -8.33
 7  2.7423631371214585E-01  1.9092977458408302E+00  -16.44  -16.41

   0.2742363137121459       1.909297745840830
```

```
#################################################################
# Checking 'newt2' using numerical root finding capablities
# of Maple.
#################################################################
sgi1% maple
    |\^/|     Maple V Release 5 (University of Texas at Austin)
._|\|   |/|_. Copyright (c) 1981-1997 by Waterloo Maple Inc. All rights
 \  MAPLE  /  reserved. Maple and Maple V are registered trademarks of
 <____ ____>  Waterloo Maple Inc.
      |       Type ? for help.
> Digits := 20;
                                  Digits := 20

> f1 := sin(x*y) - 1/2;
                              f1 := sin(x y) - 1/2

> f2 := y^2 - 6*x - 2;
                                       2
                               f2 := y  - 6 x - 2


#################################################################
# Locates root found by 'newt2 1.0 1.0'
#################################################################
> ans := fsolve( {f1,f2}, {x,y}, {x=0.25..0.30, y=1.8..2.0});
         ans := {y = 1.9092977458408301606, x = .27423631371214588082}
```

```
#################################################################
# Compute residuals of root
#################################################################
> r1 := evalf(subs(ans,f1)); r2 := evalf(subs(ans,f2));
                                                  -19
                                     r1 := -.1 10

                                                  -18
                                     r2 := -.1 10


#################################################################
# Locates root found by 'newt2 10.0 10.0'
#################################################################
> ans := fsolve( {f1,f2}, {x,y}, {x=7..9, y=6..8});
         ans := {x = 8.0480622340064835835, y = 7.09142957407312207O4}

> r1 := evalf(subs(ans,f1)); r2 := evalf(subs(ans,f2));
                                                  -18
                                    r1 := -.35 10

                                         r2 := 0
```

```
#################################################################
# Locates root found by 'newt2 100.0 100.0'
#################################################################
> ans := fsolve( {f1,f2}, {x,y}, {x=203.9..203.95, y=35.0..35.01});
         ans := {x = 203.91061457097670060, y = 35.006623479362590528}

>  r1 := evalf(subs(ans,f1)); r2 := evalf(subs(ans,f2));
                                                    -16
                                  r1 := -.5214 10

                                       r2 := 0


#################################################################
# Another nearby, but distinct, root
#################################################################
> ans := fsolve( {f1,f2}, {x,y}, {x=203..204, y=35.0..35.1});
         ans := {x = 203.95052002180667001, y = 35.01004313237617278 2}

> r1 := evalf(subs(ans,f1)); r2 := evalf(subs(ans,f2));
                                                    -16
                                   r1 := .4548 10

                                       r2 := 0

> quit;
```