```
c=============================================================
c
c     gpwave: Generates time-series of profiles of
c     left-moving "wave" (f(t+x) = constant) and outputs to
c     stdio in form suitable for susequent plotting with
c     'gnuplot'.
c
c     For parametric surface plots 'gnuplot', expects three
c     numbers per line:
c
c         x(i), y(j), f(i,j)
c
c     with all data points with the same x(i) on contiguous
c     lines (a group) and with empty lines separating
c     groups.  A quick glance at some sample output from this
c     program should make the arrangement clear.
c
c=============================================================
      program     gpwave

      implicit    none

      integer     i4arg

      integer     maxn
      parameter ( maxn = 100 )

      real*8      f
      real*8      x(maxn)
      integer     i,          j,          n,          nx,
     &            nt
      real*8      h,          t,          dt

      n = i4arg(1,-1)
      if( n .lt. 1  .or.  n .gt. maxn ) goto 900
      nx = n
      nt = n

      h = 1.0d0 / (nx - 1)
      x(1) = 0.0d0
```

```
      do j = 1 , nx - 1
         x(j+1) = x(j) + h
      end do

      t = 0.0d0
      dt = 1.0d0 / (nt - 1)
      do i = 1 , nt
         do j = 1 , nx
c-------------------------------------------------------------
c           Output the cordinates and function value, three
c           per line, first coordinate (time) constant.
c-------------------------------------------------------------
            write(*,*) t, x(j), f(mod((x(j) + t),1.0d0))
         end do
c-------------------------------------------------------------
c           Empty line separates groups with distinct
c           first coordinate.
c-------------------------------------------------------------
         write(*,*)
         t = t + dt
      end do

      stop

900   continue
         write(0,*) 'usage: gpwave <n>'
      stop

      end

c-------------------------------------------------------------
c     Gaussian function.
c-------------------------------------------------------------
      double precision function f(x)
         implicit     none
         real*8       x
         f = exp(-((x-0.5d0)/0.1d0)**2)
         return
      end
```